	RPD-311DW Whynter Elite D-Series Energy Star 30 Pint Portable Dehumidifier	RPD-451DW Whynter Elite D-Series Energy Star 45 Pint Portable Dehumidifier	RPD-711DWP Whynter Elite D-Series Energy Star 70 Pint Portable Dehumidifier with Pump
Dehumidifying Capacity	• 30 pint (14 liter) capacity dehumidifier	• 45 pint (21.3 liter) capacity dehumidifier	• 70 pint (33 liter) capacity dehumidifier
Water Bucket Capacity	• 6 pint (2.83 liter) removable water bucket	• 6 pint (2.83 liter) removable water bucket	• 13 pint (6.15 liter) removable water bucket
Adjustable Humidity Range	• 35 - 85% relative humidity	• 35 - 85% relative humidity	• 35 - 85% relative humidity
Features	• Low temperature operation (minimum ambient temperature low 40°Fs) • Auto-restart and Auto-shutoff functions • Auto-defrosting capability to prevent frost build-up inside unit • Electronic controls with humidity sensor settings • Handles and caster wheels for portability	• Low temperature operation (minimum ambient temperature low 40°Fs) • Auto-restart and Auto-shutoff functions • Auto-defrosting capability to prevent frost build-up inside unit • Electronic controls with humidity sensor settings • Handles and caster wheels for portability	• Low temperature operation (minimum ambient temperature low 40°Fs) • Auto-restart and Auto-shutoff functions • Auto-defrosting capability to prevent frost build-up inside unit • Electronic controls with humidity sensor settings • Handles and caster wheels for portability
Refrigerant	• R410A	• R410A	• R410A
Drain Method	• Direct Drain and Continuous/Gravity	• Direct Drain and Continuous/Gravity	• Direct Drain, Continuous/Gravity, and Pump
Fan Speed	• Dual fan speed	• Dual fan speed	• Dual fan speed
Air Filter	• 2 in 1 silver-coated washable pre-filter combo	• 2 in 1 silver-coated washable pre-filter combo	• 2 in 1 silver-coated washable pre-filter combo
Timer	• 24-hour timer function	• 24-hour timer function	• 24-hour timer function
Noise level	• <53 dBA	• <53 dBA	• <55 dBA
Air Flow (at high speed)	• 235m^3/h / 138 CFM	• 235m^3/h / 138 CFM	• 335m^3/h / 197 CFM
Maximum power consumption	• 440W / 3.1A	• 590W / 4.0A	• 915W / 4.6A
Power supply	• 115 V / 60Hz	• 115 V / 60Hz	• 115 V / 60Hz
Unit dimensions	• 15.2″ W x 10.8″ D x 19.7″ H	• 15.2″ W x 10.8″ D x 19.7″ H	• 16.1″ W x 11.7″ D x 24.3″ H
Package dimensions	• 16.5″ W x 11.7″ D x 21.1″ H	• 16.5″ W x 11.7″ D x 21.1″ H	• 16.8″ W x 12.9″ D x 26.5″ H
Net weight	• 30.2 lbs	• 32 lbs	• 38.6 lbs
Gross weight	• 33.1 lbs	• 35.3 lbs	• 40.3 lbs
Certification	• UL listed and Energy Star rated	• UL listed and Energy Star rated	• UL listed and Energy Star rated
UPC Code	• UPC 850956003781	• UPC 850956003798	• UPC 850956003804
Accessories	• 20" drain hose for Continuous/Gravity drain	• 20" drain hose for Continuous/Gravity drain	• 16.5' drain hose for Pump drain 20" drain hose for Continuous/Gravity drain